

Product Specifications

50EPN28FD3

PISTOL CORDED NUTRUNNER
5.6 - 28 Nm (4.1 – 20.6 ft-lbs)

PISTOL - 50 SERIES

The NeoTek™ fastening system is the next generation of smart tool solutions. The lightweight, ergonomic design along with fully programmable features such as the high-output LED light rings, audible alerts, and handle vibration all create a better user experience that leads to decreased operator fatigue and increased productivity.

FEATURES

- 1 million cycles maintenance-free*
- Repeatability & accuracy with 2.0 Cm/Cmk at +/- 7%
- 21% lighter (tool/cable system) than existing tool family
- Digital communication for reliable performance
- Internal temperature monitoring
- Configurable LED light rings
- Data logging with on-board tool memory
- Preventive maintenance alerts

SPECIFICATIONS

TORQUE RANGE (Nm)

Min / Max: 5.6 / 28

TORQUE RANGE (ft·lb)

Min / Max: 4.1 / 20.6

SPEED

r/min: 2,125

WEIGHT & DIMENSIONS

Weight 1.58 kg / 3.48 lb

Length 256 mm / 10.07 in

Side to Center 16.3 mm / 0.64 in

Output Drive 3/8" Sq. Drive

Country of Origin: Assembled in USA

