

The NeoTek™ fastening system is the next generation of smart tool solutions. The lightweight, ergonomic design along with fully programmable features such as the high-output LED light rings, audible alerts, and handle vibration all create a better user experience that leads to decreased operator fatigue and increased productivity.

FEATURES

- Repeatability & accuracy with 2.0 Cm/Cmk at +/- 7%
- 21% lighter (tool/cable system) than existing tool family
- Digital communication for reliable performance
- Internal temperature monitoring
- Configurable LED light rings
- · Data logging with on-board tool memory
- Preventive maintenance alerts

SPECIFICATIONS

TORQUE RANGE (Nm)

Min / Max: 118 / 473

TORQUE RANGE (ft-lb)

Min / Max: 87.0 / 348.8

SPEED

r/min: 250

WEIGHT & DIMENSIONS

Weight 7.60 kg / 16.76 lb Length 610 mm / 24.01 in

Side to Center 38.0 mm / 1.49 in

Output Drive 1" Sq. Drive


Country of Origin: Assembled in USA

CE

Product Specifications 70ESN475SD8

INLINE CORDED NUTRUNNER 118 - 473 Nm (87.0 - 348.8 ft·lbs)

INLINE - 70 SERIES





Phone: +1 (800) 845-5629 Phone: +1 (919) 387-0099 Phone: +49 (0)7363 81-0

www.ClecoTools.com / www.ClecoTools.de