


Złączka mosiężna prosta blokowana za pomocą opaski Brass fittings to be locked with hose clamp



Dla rur:
GF blokowane opaską
GFT blokowane opaską i pierścieniem ochronnym AP

For conduit:
GF to be locked with hose clamp
GFT to be locked with hose clamp plus protection ring AP



Zastosowanie Application



RINA



GFM - Złączka mosiężna prosta (blokowana za pomocą opaski) gwint męski calowy, PG i metryczny ISO

Kod calowy	F Gwint calowy	A mm	B mm	Kod PG	F Gwint PG	A mm	B mm	Kod metryczny ISO	F Gwint metryczny ISO	Certyfikaty	A mm	B mm	Odpowiednia do rur	Dla rury NW	Ø rury GF mm wew. zew.	Ø rury GFT mm wew. zew.	OD mm	SP mm	Opakowanie standard
GFMG10	1/4"	7	8	GFMP10PG07	7	7	8	GFM10M12	M12x1,5		7	8	GF - GFT	10	10,0 - 14,0	10,0 - 15,0	22	19	20
GFMG10A	3/8"	7	8	GFMP10PG09	9	7	8	GFM10M16	M16x1,5		7	8					22	19	
				GFMP10PG11	11	7											25,4	22	
GFMG12	3/8"	10	10	GFMP12PG11	11	7	10	GFM12M16	M16x1,5		10	10	GF - GFT	12	12,0 - 16,0	12,0 - 17,0	25,4	22	20
GFMG12A	1/2"	10	10	GFMP12PG13	13,5	7	10	GFM12M20	M20x1,5		10	10					27,5	24	
				GFMP12PG16	16	7	10										27,5	24	
GFMG15	1/2"	10	13	GFMP15PG13	13,5	7	13	GFM15M20	M20x1,5		10	13	GF - GFT	15	15,0 - 20,5	15,0 - 21,0	27,5	24	20
				GFMP15PG16	16	7	13										27,5	24	
																	34,5	30	
GFMG15A	3/4"	12	13										GF - GFT	20	20,0 - 26,0	20,0 - 27,0	31	27	10
GFMG20	1/2"	10	16	GFMP20PG13	13,5	7	16	GFM20M20	M20x1,5		10	16					31	27	
				GFMP20PG16	16	7	17										31	27	
GFMG20A	3/4"	12	17	GFMP20PG21	21	10	17	GFM20M25	M25x1,5		12	17	GF - GFT	27	27,0 - 34,0	27,0 - 35,0	34,5	30	10
GFMG27	3/4"	12	21	GFMP27PG21	21	10	23	GFM27M25	M25x1,5		12	21					41,5	36	
								GFM27M32	M32x1,5		12	23					41,5	36	
GFMG27A	1"	12	23	GFMP27PG29	29	10	23						GF - GFT	36	36,0 - 43,0	36,0 - 45,0	46	40	5
GFMG36	1"	12	26					GFM36M32	M32x1,5		12	26					50,8	44	
				GFMP36PG29	29	11	30										52	45	
GFMG40	1 1/4"	13	36	GFMP40PG36	36	13	36	GFM40M40	M40x1,5		13	35	GF - GFT	40	40,0 - 48,0	40,0 - 50,0	57,5	50	5
GFMG47	1 1/2"	15	40	GFMP47PG36	36	15	40						GF - GFT	47	47,0 - 55,0	47,0 - 57,0	67	58	5
				GFMP47PG42	42	15	42	GFM47M50	M50x1,5		15	42	GF - GFT	58	58,0 - 68,0	58,0 - 70,0	78	70	2
GFMG58	2"	15	51	GFMP58PG48	48	15	51	GFM58M63	M63x1,5		15	51							
REF. Part N. GAS	F GAS thread	A mm	B mm	REF. Part N. PG	F PG thread	A mm	B mm	REF. Part N. ISO	F ISO thread	Approvals	A mm	B mm	Fits to conduit type	Conduit code NW	int. Ø GF conduit mm	ext. Ø GF conduit mm	int. Ø GFT conduit mm	ext. Ø GFT conduit mm	Packing unit

GFM - Brass fittings to be locked with hose clamps thread male GAS, PG and ISO Metric